

FOR THE REOPENING YOUR BUSINESS - HOW TO PUT YOUR FULLY AUTOMATIC MACHINE BACK INTO OPERATION

1. Connect the coffee machine to the electricity supply
2. Open the water supply for coffee machines with water connection*
3. Switch on the coffee machine at the main switch
4. Carry out the cleaning process
5. Fill the bean and powder hopper and the milk container with fresh resources

*Recommendation: For coffee machines with water connection, flush the pre-connected water filter with approx. 10 liters of water. (This is enough for further operation of the filter. It is recommended to replace the filter if it has been in use for more than 6 months. This will eliminate all possible risks).

If the coffee machine has not been decommissioned according to the user manual, we recommend to have the recommissioning carried out by a service technician.



To contain the coronavirus, we recommend that you regularly disinfect the control panel, the front door as well as the coffee spout of your Franke coffee machine.

Disinfectant

Please only use commercial disinfectants for hands. Do not use any disinfectants designed for sanitary facilities or similar purposes!

Method of use

1. Spray a little disinfectant on a soft, damp cloth.
2. Carefully wipe the control panel, the front door and the coffee spout with the cloth.

Never spray any liquid directly onto the display to avoid damage.



MAKE IT WONDERFUL

Franke Kaffeemaschinen AG
cs-info.ch@franke.com

Franke Coffee Systems GmbH
cs-info.de@franke.com

Franke Coffee Systems Americas
cs-coffeesales.us@franke.com

Franke Coffee Systems UK
sales@Frankecoffeesystems.co.uk

coffee.franke.com