



技术要求:
1. 拉伸冲裁后表面无起皱压痕现象.
2. 产品焊接后无焊点, 脱焊现象.
2. Label 粘贴平整, 不得倾斜, 位置与图示位置.
3. 产品用透明胶袋及纸套和泡沫包装.
4. 夹子条采用激光点焊.

12	900-337		Installation manual	1	Put into bottom of bowl				
11	320-279		Installation sheet	1	Stick on back of bowl				
10	300-566		Foam rail	2	Styrofoam				
9	300-564		Foam end	2	Styrofoam				
8	310-383		Carton sleeve	1	Cardboard				
7	300-006		PE bag	1					
6	320-258		Product label	3	Stick on back of bowl and carton sleeve				
5	610-013		Sound insulation pad	1	Bitumen	0056-210927		133.0323.686	
4	620-075		Back-up clip	1		0056-210903		992.0361.954	
3	620-073		Fastfix	5	1.4310 federhart	0056-207449		992.0363.215	
2	700-126		R45 170 x 320 x 130	1	EN 1.4301	0550-100694			
1	861-132		BCX 260 SBL SFG	1	AISI 304	0056-214867			
Item		Remark		Title		Qty	Material	Drawing No.	Part_Number
Drawn by		HY003		3/6/2017		Replaced through		Weight	
Checked by		Huag		6/19/2018		Replacement for		4.755	
Modified by		Huag		3/14/2018		Originate from		Tolerance	
Revision Description:						Unit		Scale	
Revision from 3/14/2018 / Huag						Department: Entwicklung China		Material	
Add BOM list and comments for Production line.						Project		Remark	
						Bell		BCX260-10E	
						Collection		260	
						BCX 260 SBL			
						625 x 480 mm (1 TH Ø35mm)			
						3 1/2" (with hidden overflow)			
						Format	Drawing No.		Rev.
						A2	0056-214894		G
						Sheet	1		1