

Creating effortless experiences



MYTICO Vario



1 Mytico Vario Options

- Third and fourth grinder
- Powder dosing unit
- Second steam wand as Autosteam Pro S3
- Back wall with lighting
- Coffee grounds ejection assembly

2 Coffee Module

- Coffee Module right
- Coffee Module left
- Single or double coffee spout

3 Barista Module

- Steam wand Autosteam Pro S3 on the left
- Hot water spout in the center
- Traditional steam wand S1 or powder option on the right
- Barista Levers

4 Milk and Cleaning System

- FoamMaster™ (FM): hot and cold milk and milk foam, individually adjustable consistency.
- CleanMaster (CM): fully automatic cleaning system with integrated cleaning cartridge and cleaning tank.



Choice of six Franke colors for the side panels

Pure Shot dispenses the selected beverage pure and without dilution

High quality materials and aesthetic finishes



50cm
Compact height
Boosts customer interaction



Design
Traditional Italian design



iQFlow™
The groundbreaking technology that extracts more flavor for unrivaled in-cup quality

Franke Colors



Mytico Vario perfectly combines the sleek traditional Italian look with the simplicity and speed of a Franke commercial coffee machine. It can keep up with the best baristas and their craft without having to train skills so they can spend more time creating memorable coffee experiences with their customers. This high-performance machine makes a variety of beverages from different coffees, foams, types of milk and milk alternatives with its two intuitive touch screens.

CAPACITY*	SINGLE	PARALLEL
Espresso	190	335
Coffee	165	270
Cappuccino	190	335
Hot water	23l/h	

*Cups per hour according to DIN 18873



Franke Kaffeemaschinen AG
cs-info.ch@franke.com

Franke Coffee Systems GmbH
cs-info.de@franke.com

Franke Coffee Systems Americas
cs-coffeesales.us@franke.com

Franke Coffee Systems UK
sales@frankecoffeesystems.co.uk

coffee.franke.com

590.0697.075/02.23/CH-EN/Subject to dimensional, design and version changes.

Technical Data

Machine

Model	Vario
Power	380 – 415V 3LNPE 16A, 50/60Hz, 4.6 - 9.0kW
Dimensions	925 mm / 610mm / 644 mm (W / H / D)
Weight (empty)	approx. 105kg
Franke Colors	Onyx, Cotton, Sand, Burgundy, Blueberry, Basil
Cleaning System	CleanMaster

Water connection

Water connection	Metal hose with union nut G3/8", L = 1500 mm
Water supply line	If possible on installation side: untreated water of drinking water quality (not from household decalcification system)
Water pressure	80–800 kPa (0.8–8.0 bar)
Flowrate	>0.1l/sec
Water temperature	<25°C
Total hardness	4–8 °dH GH (German total hardness) / 7–14 °fH GH (French total hardness) / 70–140 ppm (mg/l)
Carbonate hardness	3–6 °dH KH (carbonate hardness) / 50–105 ppm (mg/l)
Acid content/pH value	6.5–7.5 pH
Chlorine content	< 0.5 mg/l

Water drain

Drain hose	Dia. = 16 mm, L = 2000 mm
------------	---------------------------

