



Technical Data:

Electrical connection: 220-240 VAC, 1LNPE, 1,10A, 50-60 Hz, 10 A (CH, EU, GB)
 100 VAC, 1LNPE, 1,70A, 50-60 Hz, 10 A (JP)
 110-127 VAC, 1LNPE, 1,70A, 50-60 Hz, 10 A (USA, LATAM)
 Energy loss: 2,355 kWh/24h - 220 - 240 VAC 50-60 Hz (according to DIN 18873-2)
 Cooling temperature: + 3°C to + 8°C (Milk)
 Empty weight: max. 35 kg
 Approvals: CE / CB / HACCP
 Refrigerant: R600a - 35 grams

Installation notes on side:

Socket with RCD (residual current device)
 220-240 VAC, 1LNPE, 1,10A, 50-60 Hz, 10 A (CH, EU, GB)
 100 VAC, 1LNPE, 1,70A, 50-60 Hz, 10 A (JP)
 110-127 VAC, 1LNPE, 1,70A, 50-60 Hz, 10 A (USA, LATAM)

The cooling unit must be installed in the counter under the coffee machine. By positioning the cooling unit right under the coffee machine the coffee-grounds ejection is not possible. If the coffee-grounds ejection is desired, it is possible to put the cooling unit to the left or to the right. Wall clearance of the side panels on the top min. 50 mm on the rear panel min. 100 mm.

Installation requirements:

Our delivered appliances are ready for operation. They have to be installed on a flat surface. First the preparations for the connections of water and electricity must be complete. Distance max. 1 m up to the device. This preparation-works must be performed by qualified specialists in accordance with applicable regulations. The device is intended exclusively for operation in interior rooms. Ambient temperatur: 5°C - 32°C. Humidity: max. 80%. In the counter under the coffee machine, sufficient ventilation for the cooling unit must be ensured. The maximum length of the milk lines of 1.5 m to the coffee machine must not be exceeded.

Franke Kaffeemaschinen AG Franke-Strasse 9 CH-4963 Aarburg Telefon: +41 (0) 79 2607 E-Mail: kmc@franke.com Internet: www.franke.com	Unit	NTS	Description					
	Drawn	MB002	13.08.2020	TD_UT40_CM_en				
	Modified	MB002	28.01.2021					
	Checked		01.01.1970					
ECN	500000001512	Document ID - Version		Revision	Status	Sheet / Sheets	Format	
Article Number		20194836-01		15	1 / 1	A2		